

Amendments to the claims are as follows:

1. (Currently Amended) An electroacoustic transducer comprising a plane diaphragm and a vibration-generating source for vibrating the diaphragm,

wherein the diaphragm supports the vibration-generating source in the vicinity of one end of ~~the~~ backside thereof, at least the one end and two sides of the diaphragm, which are perpendicular to the one end and are opposite to each other, are supported on an elastic cushion member, one side of the elastic cushion member supports the diaphragm, and ~~an opposing~~ the other side thereof is supported on ~~the~~ base opposite to the diaphragm, and

wherein the diaphragm is vibrated in a direction perpendicular to the plane of the diaphragm when the vibration-generating source is driven.

2. (Currently Amended) An electroacoustic transducer according to Claim 1,

wherein the vibration-generating source includes a magnet separated from the backside of the diaphragm by a predetermined gap, and a coil wound along an outer peripheral surface of the magnet so as to be separated from ~~the~~ an outer peripheral surface of the magnet by a predetermined gap,

wherein the coil is fixed to the backside of the diaphragm, the magnet is mounted on a first plate-shape yoke, the first yoke is supported on a connecting member fixed to the backside of the diaphragm, and a gap is formed between the first yoke and the base.

3. (Original) An electroacoustic transducer according to Claim 2,

wherein the magnet is formed in a horizontally long shape in parallel to the one end of the diaphragm, the coil is wound in the horizontally long shape along the outer peripheral surface of the magnet, and a portion of the first

yoke protruding from both ends of the coil in a longitudinal direction is supported on the backside of the diaphragm by the connecting member.

4. (Currently Amended) An electroacoustic transducer according to Claim 2, ~~or 3,~~

wherein the connecting member is formed of an elastic member.

5. (Currently Amended) An electroacoustic transducer according to Claim 1,

wherein a second yoke is stacked on the magnet on ~~at~~ the side opposite to the backside of the diaphragm, and a gap is formed between the second yoke and the backside of the diaphragm.

6. (Currently Amended) An electroacoustic transducer according to any one of Claims 1, ~~to 5,~~

wherein ~~an~~ the other end opposite to the one end of the diaphragm is supported on a rigid body.

7. (Currently Amended) An electroacoustic transducer according to any one of Claims 1, ~~to 6,~~

wherein push button switches are provided in the vicinity of ~~an~~ the outer peripheral edge on the surface of the diaphragm.

8. (Currently Amended) An electronic apparatus comprising an electroacoustic transducer including a vibration-generating source for vibrating a diaphragm, and a body case for mounting the electroacoustic transducer,

wherein the diaphragm is vibrated in a plane direction perpendicular to the diaphragm, and the body case is provided with a concave portion on which the electroacoustic transducer is mounted at a predetermined depth from atthe surface of the body case, and

wherein, when the electroacoustic transducer is mounted in the concave portion, anthe outer peripheral edge of the base is guided in atthe bottom of the concave portion, and a predetermined gap is formed between anthe outer peripheral edge of the diaphragm and anthe inner peripheral surface of the concave portion.

9. (Currently Amended) An electronic apparatus according to Claim 8, wherein atthe size of the base is formed to be larger than that of the diaphragm.

10. (Currently Amended) An electronic apparatus according to Claim 8,

wherein the base has the same size and shape as the diaphragm, and the concave portion comprises a first concave portion of a size to make the outer peripheral edge of the base guidable and a second concave portion formed to be larger than the first concave portion such that a predetermined gap is formed between the second concave portion and the outer peripheral edge of the diaphragm.

11. (Original) An electronic apparatus according to Claim 8, wherein the inner peripheral surface of the concave portion is formed in a tapered shape, the base is guided in the bottom of the concave portion, and a predetermined gap is formed between the outer peripheral edge of the diaphragm and the inner peripheral surface of the concave portion.

12. (New) An electroacoustic transducer according to Claim 3,
wherein the connecting member is formed of an elastic member.

13. (New) An electroacoustic transducer according to any one of
Claim 2,
wherein an end opposite to the one end of the diaphragm is supported
on a rigid body.

14. (New) An electroacoustic transducer according to any one of
Claim 3,
wherein an end opposite to the one end of the diaphragm is supported
on a rigid body.

15. (New) An electroacoustic transducer according to any one of
Claim 4,
wherein an end opposite to the one end of the diaphragm is supported
on a rigid body.

16. (New) An electroacoustic transducer according to any one of
Claim 5,
wherein an end opposite to the one end of the diaphragm is supported
on a rigid body.

17. (New) An electroacoustic transducer according to any one of
Claim 12,
wherein an end opposite to the one end of the diaphragm is supported
on a rigid body.

18. (New) An electroacoustic transducer according to any one of Claim 2,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

19. (New) An electroacoustic transducer according to any one of Claim 3,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

20. (New) An electroacoustic transducer according to any one of Claim 4,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

21. (New) An electroacoustic transducer according to any one of Claim 5,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

22. (New) An electroacoustic transducer according to any one of Claim 6,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

23. (New) An electroacoustic transducer according to any one of Claim 12,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

24. (New) An electroacoustic transducer according to any one of Claim 13,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

25. (New) An electroacoustic transducer according to any one of Claim 14,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

26. (New) An electroacoustic transducer according to any one of Claim 15,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

27. (New) An electroacoustic transducer according to any one of Claim 16,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

28. (New) An electroacoustic transducer according to any one of Claim 17,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

29. (New) An electroacoustic transducer according to any one of Claim 18,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

30. (New) An electroacoustic transducer according to any one of Claim 20,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

31. (New) An electroacoustic transducer according to any one of Claim 21,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.

32. (New) An electroacoustic transducer according to any one of Claim 22,

wherein push button switches are provided in the vicinity of an outer peripheral edge on the surface of the diaphragm.